

Tilt Angle: 10° ~ -60°

1ST BOOM SECTION - FLY JIB - ANGLE RATED NET RATED LOADS (KG) AT EXTENSION JIB ANGLE

	2ND BOOM SECTION - FLY JIB - ANGLE RATED							
ı	NET RATED LOADS (KG) AT EXTENSION JIB ANGLE							
	BOOM ANGLE (DEG)	10°	0°	-20°	-40°	-60°		
	78°	850	850	850	850	850		
	70°	850	850	850	850	800		
	60°	750	750	750	750	750		
	50°	750	750	750	730	730		
	40°	660	660	620	610	610		
ľ	30°	540	540	530	530	560		
	20°	480	480	470	470	470		
	10°	440	440	440	440	440		
١	0°	430	430	430	430	430		

3KD BOOM SECTION - FLT JIB - ANGLE KATED								
NET RATED LOADS (KG) AT EXTENSION JIB ANGLE								
BOOM ANGLE (DEG)	10°	0°	-20°	-40°	-60°			
78°	750	750	750	750	750			
70°	750	750	750	750	750			
60°	750	750	720	670	660			
50°	580	580	530	520	520			
40°	440	440	410	410	410			
30°	340	340	330	330	330			
20°	270	270	270	270	270			
10°	240	240	240	240	240			
0°	220	220	220	220	220			

	411 DUUM SECTION - FLT JID - ANGLE KATED							
	NET RATED LOADS (KG) AT EXTENSION JIB ANGLE							
	BOOM ANGLE (DEG)	10°	0°	-20°	-40°	-60°		
	78°	750	750	750	750	750		
	70°	750	750	720	650	620		
	60°	500	500	450	420	420		
	50°	310	310	290	280	280		
ı	40°	220	220	210	210	210		
	30°	160	160	160	160	160		
	20°	140	140	130	130	130		
	10°	110	110	110	110	110		
	0°	70	70	70	70	70		

JIN DOOM SECTION - FLI JID - ANGLE RATED							
NET RATED LOADS (KG) AT EXTENSION JIB ANGLE							
BOOM ANGLE (DEG)	10°	0°	-20°	-40°	-60°		
78°	750	750	720	600	540		
70°	330	330	280	250	240		
60°	140	140	120	120	110		

OTH DOUM SECTION - FLT JID - ANGLE RATED							
NET RATED LOADS (KG) AT EXTENSION JIB ANGLE							
BOOM ANGLE (DEG)	10°	0°	-20°	-40°	-60°		
78°	670	670	410	310	280		
70°	210	210	180	160	150		
60°	70	70	60	60	60		

MAX CAPACIT	Y: Ö	JUK	g	
JIB LENGTH:	2.37	4 m	~ 5	.574n
TILT ANGLE:	10°	~ -6	60°	
MASS OF JIB	& H00	K: 3	00k	g

